





Interactive Display Solutions



 65" 75" 86"

-  Effortless import of various file types
-  Handwriting and shape identification
-  Export include Image, Word, PowerPoint, and PDF formats
-  Comprehensive editing features for images and videos



Quad Core CPU



Android 13



8 GB RAM
128 GB ROM



Collaborate like never before!



TRANSFORMING EDUCATIONAL SPACES

Empower Your Students & Teachers

Interactive panels in classrooms enable collaborative, **seminar-style** teaching that sparks student creativity.

- Enhancing the Educational Experience
- Nurturing intuitive based Learning
- Interactive Classroom Instruction
- Immersive Learning Journey
- Empowering Student Participation

EMPOWERING BUSINESS GROWTH

Transform The Way You Collaborate

We provide comprehensive **Audio Visual** solutions to organisations, helping them reach new heights.

- Streamline Your Team Communication
- Enhancing Client Presentations
- Complex Data Visualization
- Active Audience Participation
- Interactive Meeting Presentations



PRODUCT SPECIFICATION

	SPECS	65 Inch	75 Inch	86 Inch
DISPLAY	Panel Type	ADS	ADS	ADS
	Back Light Unit	DLED	DLED	DLED
	Response Time	4ms	4ms	4ms
	Aspect Ratio	16:09	16:09	16:09
	Display Area(HxV)	1428.48(H)×803.52(V)mm	1649.664(H)×927.936(V)mm	1895.04(H)×1065.96(V)mm
	Pixel Pitch	0.372(H)×0.372(V)mm	0.4296(H)×0.4296(V)mm	0.4935(H)×0.4935(V)mm
	Resolution	3840×2160	3840×2160	3840×2160
	Refreshing Frequency	60Hz	60Hz	60Hz
	Display Color	1.07B	1.07B	1.07B
	Bit Rate	10bit	10bit	10bit
	NTSC Gamut	72%	72%	72%
	Contrast Ratio	1200:1	1200:1	1200:1
	Viewing Angle	178°(H/V)	178°(H/V)	178°(H/V)
	Brightness with glass(min)	400 cd/m ²	400 cd/m ²	400 cd/m ²
	Brightness with glass(typ)	450 cd/m ²	450 cd/m ²	450 cd/m ²
Life Time	≥ 50000 Hours	≥ 50000 Hours	≥ 50000 Hours	
OPERATING SYSTEM	System Version	Android 13.0	Android 13.0	Android 13.0
	RAM	8GB	8GB	8GB
	ROM	128GB	128GB	128GB
	CPU	Quad-core ARM Cortex (A55)	Quad-core ARM Cortex (A55)	Quad-core ARM Cortex (A55)
	GPU	Mali G52MP2	Mali G52MP2	Mali G52MP2
TOUCH SYSTEM	Sensing Type	Infrared recognition	Infrared recognition	Infrared recognition
	Touch Recognition	Finger,Passive infrared pen	Finger,Passive infrared pen	Finger,Passive infrared pen
	Accuracy	±1.5mm	±1.5mm	±1.5mm
	Touch Point	40	40	40
	Minimum object Size	3mm	3mm	3mm
	Writing Height	≤ 3mm	≤ 3mm	≤ 3mm
Supporting OS	Windows/ Android/ Linux/ macOS / Chrome			
AUDIO	Audio Output	2.0	2.0	2.0
	Output Power	2×16W	2×16W	2×16W
POWER	Power Supply	100-240V~50/60Hz	100-240V~50/60Hz	100-240V~50/60Hz
	Power Consumption (Typ/Max)	160/ 320W	200/ 360W	350/ 520W
	Standby Power	≤ 0.5W	≤ 0.5W	≤ 0.5W
I/O Interface	HDMI IN	3	3	3
	HDMI OUT	1	1	1
	USB 2.0	1	1	1
	USB Player (Media) type-C	1	1	1
	USB 3.0	4	4	4
	TOUCH OUT	2	2	2
	VGA IN	1	1	1
	Audio/Mic IN	1	1	1
	Audio Out	1	1	1
	SPDIF	1	1	1
	RS232	1	1	1
	RJ45 IN	1	1	1
RJ45 OUT	1	1	1	
PHYSICAL SPECIFICATIONS	Dimension (L×H×D)	1488.4×896.6×87.2mm	1709×1020×88mm	1957×1160×100mm
	Package Dimension (L×W×H)	1628×208×1005mm	1863×225×1140mm	2110×225×1283mm
	VESA	600×400mm	800×400mm	800×600mm
	Net Weight	34.95Kg	47.30Kg	58.55Kg
	Gross Weight	44.70Kg	60.55Kg	75.90Kg
ACCESSORIES	Power Cord	1	1	1
	HDMI Cable	1	1	1
	USB Touch Cable (Type A-B)	1	1	1
	Remote Control	1	1	1
	Writing Pen	2	2	2
ENVIRONMENTAL CONDITIONS	Operating Temperature	0 Ć - 40 Ć	0 Ć - 40 Ć	0 Ć - 40 Ć
	Operating Humidity	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH
	Storage Temperature	-20 Ć - 60 Ć	-20 Ć - 60 Ć	-20 Ć - 60 Ć
	Storage Humidity	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH
	Altitude	Below 5000 meter	Below 5000 meter	Below 5000 meter
OPTIONAL PC MODULE	PC Module	OPS62A	OPS62A	OPS62A
	Wireless Module	SI07	SI07	SI07
CERTIFICATION	BIS, EMC, CE, FCC, UKCA			